

58.05  
Historic  
13/04/2017  
VC136  
58.05-1  
Historic  
04/05/2022  
VC210

**ON-SITE AMENITY AND FACILITIES**

**Accessibility objective**

To ensure the design of dwellings meets the needs of people with limited mobility.

**Standard D18**

At least 50 per cent of dwellings should have:

- A clear opening width of at least 850mm at the entrance to the dwelling and main bedroom.
- A clear path with a minimum width of 1.2 metres that connects the dwelling entrance to the main bedroom, an adaptable bathroom and the living area.
- A main bedroom with access to an adaptable bathroom.
- At least one adaptable bathroom that meets all of the requirements of either Design A or Design B specified in Table D7.

**Table D7 Bathroom design**

	Design option A	Design option B
Door opening	A clear 850mm wide door opening.	A clear 820mm wide door opening located opposite the shower.
Door design	Either: <ul style="list-style-type: none"> <li>▪ A slide door, or</li> <li>▪ A door that opens outwards, or</li> <li>▪ A door that opens inwards that is clear of the circulation area and has readily removable hinges.</li> </ul>	Either: <ul style="list-style-type: none"> <li>▪ A slide door, or</li> <li>▪ A door that opens outwards, or</li> <li>▪ A door that opens inwards and has readily removable hinges.</li> </ul>
Circulation area	A clear circulation area that is: <ul style="list-style-type: none"> <li>▪ A minimum area of 1.2 metres by 1.2 metres.</li> <li>▪ Located in front of the shower and the toilet.</li> <li>▪ Clear of the toilet, basin and the door swing.</li> </ul> The circulation area for the toilet and shower can overlap.	A clear circulation area that is: <ul style="list-style-type: none"> <li>▪ A minimum width of 1 metre.</li> <li>▪ The full length of the bathroom and a minimum length of 2.7 metres.</li> <li>▪ Clear of the toilet and basin.</li> </ul> The circulation area can include a shower area.
Path to circulation area	A clear path with a minimum width of 900mm from the door opening to the circulation area.	Not applicable.
Shower	A hobless (step-free) shower.	A hobless (step-free) shower that has a removable shower screen and is located on the furthest wall from the door opening.
Toilet	A toilet located in the corner of the room.	A toilet located closest to the door opening and clear of the circulation area.

**58.05-2**

Historic  
04/05/2022  
VC210

**Building entry and circulation objectives**

To provide each dwelling and building with its own sense of identity.

To ensure the internal layout of buildings provide for the safe, functional and efficient movement of residents.

To ensure internal communal areas provide adequate access to daylight and natural ventilation.

**Standard D19**

Entries to dwellings and buildings should:

- Be visible and easily identifiable.
- Provide shelter, a sense of personal address and a transitional space around the entry.

The layout and design of buildings should:

- Clearly distinguish entrances to residential and non-residential areas.
- Provide windows to building entrances and lift areas.
- Provide visible, safe and attractive stairs from the entry level to encourage use by residents.
- Provide common areas and corridors that:
  - Include at least one source of natural light and natural ventilation.
  - Avoid obstruction from building services.
  - Maintain clear sight lines.

**Decision guidelines**

Before deciding on an application, the responsible authority must consider:

- The design response.
- The useability and amenity of internal communal areas based on daylight access and the natural ventilation it will receive.

**58.05-3**

Historic  
04/05/2022  
VC210

**Private open space objective**

To provide adequate private open space for the reasonable recreation and service needs of residents.

**Standard D20**

A dwelling should have private open space consisting of at least one of the following:

- An area at ground level of at least 25 square metres, with a minimum dimension of 3 metres and convenient access from a living room.
- A balcony with at least the area and dimensions specified in Table D8 and convenient access from a living room.
- An area on a podium or other similar base of at least 15 square metres, with a minimum dimension of 3 metres and convenient access from a living room.
- An area on a roof of 10 square metres, with a minimum dimension of 2 metres and convenient access from a living room.

If a cooling or heating unit is located on a balcony, the minimum balcony area specified in Table D8 should be increased by at least 1.5 square metres.

## HOBSONS BAY PLANNING SCHEME

If the finished floor level of a dwelling is 40 metres or more above ground level, the requirements of Table D8 do not apply if at least the area specified in Table D9 is provided as living area or bedroom area in addition to the minimum area specified in Table D11 or Table D12 in Standard D25.

**Table D8 Balcony size**

Orientation of dwelling	Dwelling type	Minimum area	Minimum dimension
North (between north 20 degrees west to north 30 degrees east)	All	8 square metres	1.7 metres
South (between south 30 degrees west to south 30 degrees east)	All	8 square metres	1.2 metres
Any other orientation	Studio or 1 bedroom dwelling	8 square metres	1.8 metres
	2 bedroom dwelling	8 square metres	2 metres
	3 or more bedroom dwelling	12 square metres	2.4 metres

**Table D9 Additional living area or bedroom area**

Dwelling type	Additional area
Studio or 1 bedroom dwelling	8 square metres
2 bedroom dwelling	8 square metres
3 or more bedroom dwelling	12 square metres

### Decision guidelines

Before deciding on an application, the responsible authority must consider:

- The design response.
- The useability and functionality of the private open space, including its size and accessibility.
- The amenity of the private open space based on the orientation of the lot, noise exposure, the wind conditions and the sunlight it will receive.
- The availability of and access to public or communal open space.
- The useability and functionality of any additional living area or bedroom area, including its size and layout.

**58.05-4**  
Historic  
04/05/2022  
VC210

### Storage objective

To provide adequate storage facilities for each dwelling.

### Standard D21

Each dwelling should have convenient access to usable and secure storage space.

## HOBSONS BAY PLANNING SCHEME

The total minimum storage space (including kitchen, bathroom and bedroom storage) should meet the requirements specified in Table D10.

**Table D10 Storage**

<b>Dwelling type</b>	<b>Total minimum storage volume</b>	<b>Minimum storage volume within the dwelling</b>
Studio	8 cubic metres	5 cubic metres
1 bedroom dwelling	10 cubic metres	6 cubic metres
2 bedroom dwelling	14 cubic metres	9 cubic metres
3 or more bedroom dwelling	18 cubic metres	12 cubic metres

### **Decision guidelines**

Before deciding on an application, the responsible authority must consider:

- The design response.
- The useability, functionality and location of storage facilities provided for the dwelling.